



www.rustins.co.uk

PRODUCT DATA SHEET

Product	Quick Dry Outdoor Danish Oil
Type	Quick Drying Outdoor Danish Oil is a unique water-borne blend of natural plant oils and other special ingredients to nourish and protect all types of exterior timber. The Oil dries with a low lustre finish.
Intended Use	For all kind of exterior timber, doors, joinery, and garden furniture.
Special Features	Brings out the natural beauty of wood and veneered surfaces. Gives a natural opengrained lustrous finish. Easy to maintain. Conforms to Plastic materials and Articles in contact with Food (England) Regulations 2008.
Preparation	The wood must be clean, smooth, dry and free from wax, dust and contaminants. Remove wax by scrubbing with White Spirit or Rustin's Surface Cleaner and a scouring pad, then wipe away whilst still wet with clean rags. Existing paint and varnishes should be removed with Rustin's Strypit Paint and Varnish Stripper . Bare wood may be dyed before coating with Rustin's Wood Dye .
Application	Apply liberally with a clean rag or brush and wipe off the surplus oil after a few minutes. The first coat should be applied liberally with a brush and allowed to dry without wiping. Nibs may be removed from the final coat by applying the oil with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus with clean rags or paper kitchen towels.
Coats	Bare wood requires 3 coats. Exterior soft wood may require extra coats.
Drying Time	2-3 hours depending on temperature and humidity.
Re-coating Time	Re-coat once the previous coat is dry.
Application Temp.	Ideally 15-25°C, do not apply below 10°C or if rain is expected.
Coverage	About 13sq.m per litre, 1 coat, depending on the absorbency of the wood.
Maintenance	Re-coat once the previous coat is dry.
Compatibility	Outdoor Danish Oil may be used over the following Rustin's products. Wood Dye, Grainfiller, and Woodfiller. Rustin's Polyurethane Varnish may be applied over Rustin's Outdoor Danish Oil at any time. The surface must be clean before varnishing.
Important Instructions for Exterior Wood	The timber will require re-oiling at least annually; horizontal surfaces and very exposed locations may require more frequent attention. Oak and softwoods are prone to weather staining caused by moisture activating mould spores present naturally in the wood. Extra coats will be required initially to effectively seal these timbers; especially areas of endgrain.
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal cool, dry conditions.
Hazards	Keep out of reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. Important: Rags used for oiling should be laid out flat to dry; otherwise they may catch fire due to spontaneous combustion.
Clean-Up	Clean brushes with warm water and detergent. If dried on, clean brushes with Rustins Brush Restorer .
Sizes	500ml 1litre